



International Course on Architectural Design
Second Level Degree Course

ARCHITECTURE and ENVIRONMENT LAB | ENVIRONMENTAL DESIGN

Computational Materiality for Sustainable Architectures and Comprehensive Skins

MODELING CLIMATE, SITE, and ARCHITECTURE


GREEN METRICS AND DIGITAL OPTIONEERING IN THE EARLY STAGE


Prof. Arch. Giuseppe Ridolfi, PhD


LECTURE #02

SKETCHING • DRAWING • DRAFTING • MODELING • DESIGNING •












Walter Gropius «the Expansible House»


INVESTIGATION • RESEARCH LEARNING • KNOWING


Piero della Francesca. De Prospettiva Pingendi (1472-76)



MODELING: the Language of Design







Leonardo da Vinci. Anatomical drawings (around 1510)

Mark. Force visualization on Gothic Cathedra

Riccardo Morandi. Bridge studies (1987/89)

Simulation of materiality in order to understand how it works



"What real function the pea has in the whistle"

Stuart Ruskin (1819-1900)




"Design is not just what it looks like and feels like. Design is how it works."

S. Jobs (1955-2011)




PERFORMANCE DESIGN






VISUALIZING MATTER

Functionality and Performance Design








- 1 Soap film model of an arch-supported membrane.
- 2 Soap-film model of a membrane surface with rope loop as its high point.
- 3 Computer simulation of a minimal surface with rope loop.

DIAGRAM: THE ABSTRACT MACHINE

..a map of relations between forces"

Deleuze, A Thousand Plateaus (1988)




AKT, South Bank Pavilion (Zaha Hadid). Load paths. © Adams Kara Taylor (AKT).



OPTIONEERING







20 months including:

- Demolition of Waldorf Astoria Hotel
- Design
- Autorizations
- Financing
- Construction (1 year and 45 days)

Empire State Building

Fast tracking

Project Management (P/M) or

Design and Manage. (D&M)

Just in Time

Lean Production

Integrated Delivery Project (IPD)

What if?

Optioneering

defining the final solution through the evaluation of alternatives

From September the16th to October the 3^d, 1929 16 alternatives (2 by day) were delivered and compared: The night of the last day the 17th solution (the Solution K) was approved



Computational Design as a scientific research





MODELING FOR SIMULATION

"This process is similar to the scientific process, which involves asking questions, framing a solvable experiment to answer the question, testing, and intepreting the results" K. Andersonn



louis kahn sketches






Decision-Making through:

- -rules of thumb
- -individual intuition
- -experience & tacit knowledge





16

Early design section through the reading room of the Net Zero Energy-designed West Berkeley Library. The design team used a combination of intuition and design simulation to create a roof form that correctly balanced the space for renewable energy, deep light wells, and natural ventilation. See case studies 8.2 and 9.1.


Source: Concept sketch by Edward Dean, courtesy of Harley Ellis Devereaux Architects.

The traditional architectural approach is a limited iterative process based on qualitative analogies



Computational Design as a scientific research

Decision-Making through:
-formal procedures
-evidence-based observation
-benchmarking




Computational Design for modeling simulation

Parametric computation= a procedure where the model is structured through constraints, parameters, instances and variables representing and affecting phenomenological attributes such as geometry, physical property, users behaviours,...

Evolutionary computation= a procedure based on trial and error problem solvers with automatic metaheuristic or stocastic optimization




Evolutionary Design, Grassohopper






Evolutionary Design, Grassohopper






GROWING PROCESS:


solving the condition:





solving the condition:




following the direction:











"For me, it is calculus that was the subject of the issuu and it is the discovery and implementation of calculus by architects that continue to drive the field in terms of formal and constructed complexity" (G. Lynn)

We are at the point that is possible to inform matter for predictable behaviors. Informing matter is not anymore and only the production of materials with predictable or definitive forms; materials do not come to live through designing forms, assigning meaningful, visible and understandable forms to matter, assigning univocity, and worshipping the aura.

Today, mastering the matter, is an activity that takes place at the structural level, dealing with relationships, parameters, forces, and energy fields expressed and formulated through the numerical *matema*.

With new technological abilities we are now able to produce *materia operata* (materials), and even *materia prima* (matters), that can be invisible, with multiple possible shapes, able to incorporate performative (more than connotative) information.


As a result we deal with «performative informed un-materiality»: materials «farcé» of that special untouchable matter that is the knowledge; for this reason we can define objects mainly made of un-materiality, able to incorporate information, memories; able to mutate dynamically presented that it is the knowledge; for this reason we can define objects mainly made of un-materiality, able to incorporate information, memories; able to mutate dynamically presented that it is the knowledge; for this reason we can define objects mainly made of un-materiality, able to incorporate information, memories; able to mutate dynamically presented that it is the knowledge; for this reason we can define objects mainly made of un-materiality, able to incorporate information, memories; able to mutate dynamically presented that it is the knowledge; for this reason we can define objects mainly made of un-materiality, able to incorporate information, memories; able to mutate dynamically presented that it is the knowledge; for this reason we can define objects mainly made of un-materiality, able to incorporate information, memories; able to mutate dynamically presented that it is the knowledge; for this reason we can define objects mainly made of un-materiality.

MODELING FOR SIMULATION NUMERICALLY PERFORMANCE BASED

features:

precision objectivity replicability communicability


More than that digital tools give us an holistic and visual perception of fenomena in order to have a faster comprehension of a large quantity of aspects.




EVIDENCE OF PROOF AND CONTROL OF THE PROCESS

Today there are a lot of software to approach and modeling architectural designing That are very intuitive and give the opportunity also to architects to run some technical analysis that in the past were served to enginnering and specialist

As a result architect today can use this tool to inform their project, deciding on evidence of test, controlling the machinery for the fabrication (files to factory)








2.3 and 2.4

Andrew Marsh, creator of Ecotect, has been experimenting with real-time, on-line daylighting simulation. The room and windows can be adjusted to see real-time daylight factor results.

Source: Courtesy of Andrew Marsh. http://andrewmarsh.com/blog/ 2010/04/11/real-time-dynamicdaylighting.

Powerful tools for gamers



PLAYING OPTIONS AND UNDERSTANDING CAUSALITY

http://andrewmarsh.com



The art of digital modeling for evaluation purpose

MAIN ASPECTS TO CONSIDER IN DIGITAL MODELING FOR SIMULATION

- Extension
- Deepeness
- Operability

- Accuracy
- Reliability


Level of details => run time* vs accuracy > many tests vs few detailed solutions

*Run time= amount of time that a computer needs to run the task




It is important to note that Building Energy Modeling is a computer program and the accuracy of results would largely depend on the inputs provided to the model. In this context, one should be mindful of the expression 'garbage-in-garbage-out'.





While a whole building energy simulation estimates the performance for an entire building, representative floors are typically modeled, including the lowest (1), middle (2), and top floors (3) of a high-rise, with multipliers being used to account for the other floors. Each atypical floor is modeled separately. Shoebox modeling analyzes a single floor or space within a floor for energy performance. For instance, a corner of a building (4) that may be exposed to solar energy from multiple directions can be tested for comfort and energy performance. A shoebox model can also be used to estimate and improve the energy use of smaller or unique spaces (5). Any scale can be studied more quickly with a single-aspect analysis, including an entire building, a single floor, or unique condition.

Source: Photo of LEED Gold certified MixC Chengdu © 2012 Callison LLC.



SHOEBOX ANALYSIS

- 1-Set boundary conditions able to represent meaningful or critical parts, systems, aspects of the building
- 2-Set adiabatic perimeters
- 3-Iterative input of different conditions in order to test different behaviours
- 4. Run analysis
- 5. Analize and evaluate



OTHER TYPES OF MODELING FOR SIMULATION


STATIC

DINAMIC


TIME-STEP analysis = over a period of time hour season, year

POINT-IN-TIME (PIT) analysis= in a precise single moment segment like hottest hours






WHICH LEVEL OF DETAIL IS REQUIRED IN THE EARLY STAGE THE BIM PROCESS



WHICH LEVEL OF DETAIL IS REQUIRED IN THE EARLY STAGE THE BIM PROCESS



MANAGEMENT OF DIGITAL MODEL LOD phases can be summarized as follows.

LOD 100: Modeled elements are at a conceptual point of development. Information can be conveyed with massing forms, written narratives, and 2D symbols.

LOD 200: Modeled elements have approximate relationships to quantities, size, location, and orientation. Some information may still be conveyed with written narratives.

LOD 300: Modeled elements are explained in terms of specific systems, quantities, size, shape, location, and orientation.


LOD 400: Continuation of LOD 300 with enough information added to facilitate fabrication, assembly, and installation.

https://sustainabilityworkshop.autodesk.com/buildings/project-phases-level-development

LOD 500: Modeled elements are representative of as installed conditions and can be utilized for ongoing facilities management.



BIM FOR INTEGRATED DELIVERY PROJECT BIM Stage 1: BIM Stage 2: BIM Stage 3: Status of AEC industry before the object-based model-based network-based Integrated Project Delivery, the long-term goal of BIM implementation implementation of BIM (manual, 2D or 3D CAD) MODELLING COLLABORATION INTEGRATION PRE-BIM ► IPD (Succar, 2008) DATASET OF FACTS **ELEMENTS / LIBRARIES**





BIM FOR INTEGRATED DELIVERY PROJECT (IPD)

- We need to go with an engineering-integrated process since the early stage
- > Bim is a chance. Is not a new and more efficent way of production
- > It is a way to integrated specialisms, to have a comprehensive view of the whole
- > Building and more than that a view to anticpate the construction and all the problems and conflicts that can arise on the site.
- It is a way to visualize materiality and for that reason to have an understanding on how the building works.
- ➤ BIM and object oriented computing in general are providing us a way to get an holistic approach to deisng

BIM allows us to integrate time, costs, manufacturing, facility management and maintanance information; to check conflicts.

More than that BIM let us to anticipate decisions, evaluate alternatives and their effects, to extend and speed up optioneering

It's a way to be aware about our decisions



BIM SOFTWARE

- 1. Autodesk provides various BIM software programs such as Revit for archi- tectural design, Mechanical, Electrical and Plumbing (MEP), and structural engineering as well as cloud based solutions such as BIM360. Visit for more information: http://www.autodesk.com/.
- 2. Bentley Systems also provides a suite of BIM tools: https://www.bentley.com/.
- 3. DProfiler by Beck technology: http://www.beck-technology.com/.
- 4. ArchiCAD by Graphisoft: http://www.graphisoft.com/.
- 5. Vectorworks Designer by Nemetschek: http://www.nemetschek.net/.
- 6. Tekla Structures: http://www.tekla.com/.
- 7. Google Sketchup Pro: http://www.sketchup.google.com/.
- 8. Affinity by Trelligence: http://www.trelligence.com/.
- 9. Vico Office: http://www.vicosoftware.com/.
- 10. Digital Project by Gehry technologies: http://www.gehrytechnologies.com/.



Testing the trade-off in order to be aware of how configurations and elements can affect behaviours.



Testing the trade-off in order to be aware of how configurations and elements can affect behaviours.

Digital Modeling give us ethical responsabilities of our choices based on evidence of proof



Ethical responsibility about us and the environment we live

Because the built environment and constructions are one of the largest factor that affect our environment


Inside the US Constructio, Buildings sector represents:

49% Energy consumption

77% Electricity consumption

47% Carbon Dioxide emission






For architects reducing impacts is a big ethical responsability

According *Architecture 2030 Program* in 2035 75% of building will be renovated or rebuilt



ENVIRONMENTAL DESIGN USING MASS COMPUTATIONAL MODELING






Class Text-books
For other resources check Mailab class portal out




ENVIRONMENTAL SYSTEM DETERMINANTS





Modeling Climate, Weather, Site, Users and Architectures.

Environmental elements that affect people's comfort




View Security

.....

NOT NATURAL FACTORS




MODELING FOR PASSIVE DESIGN




The term 'Passive Design' here refers to design strategies, technologies and solutions that effectively take advantage of the environmental conditions outside the building to maximise the energy and cost savings while ensuring the core building facilities and provisions (such as indoor comfort, safety, health, etc.) are not compromised. The environmental conditions can provide several advantages or disadvantages to the building such as the following:

- Day lighting: can reduce the energy used for artificial lighting but excessive and improper exposure may result in glare and other forms of visual discomfort
- Natural ventilation: can reduce mechanical ventilation energy to move air around but can result in hygiene issues and over-cooling in cold climates
- Natural cooling: to reduce the need for excessive airconditioning or mechanical cooling in hot climates
- Natural heating: to use the energy from the sun to provide heat indoors in cold climates instead of providing excessive artificial heating. But this needs to be managed in hot climates to reduce air-conditioning energy use
- Shading: (from trees or neighbouring buildings) can reduce heat from direct sun exposure in hot climates but can obstruct views and natural light and heat in cold climates.

MODELING FOR PASSIVE DESIGN



MODELING FOR PASSIVE DESIGN



Massing contribution to a passive design

- 1. Building location and orientation on the site
- 2. Building layout and form
- 3. Building envelope (windows, walls, roof, insulation and shading).



USING MASS COMPUTATIONAL MODELING FOR PRELIMINARY ENERGY ASSESSMENT

WHY?:

Initial mass modeling address fundamental design parameters, including the building envelope, orientation and form, typically without including mechanical or electrical systems in a manner it can speed up analysis and allow the evaluation of many different alternatives.

It provides crucial design guidance and useful feedback to the design team on how the form, orientation, programmatic strategies, and other variables will likely affect the project's performance in terms of energy, daylighting, comfort, and other design characteristics.



USING MASS COMPUTATIONAL MODELING FOR PRELIMINARY ENERGY ASSESSMENT

Energy modeling and simulation tools allow the design team to evaluate the energy performance of the building in the virtual environment considering its geometrical model, design parameters, occupancy schedules and local weather conditions.

WHAT & HOW TO MODEL:

- ENERGY
- CLIMATE
- BUILDING
- SITE
- USERS' BEHAVIOUR
- COMFORT



AVAILABLE COMPUTATIONAL TOOLS FOR ENERGY MODELING

ENERGY ANALYSIS SOFTWARE

- EnergyPlus by the U.S. Department of energy (free tool), available at: https:// energyplus.net/.
- IES Virtual Environment (VE): http://www.iesve.com/.
- eQUEST, quick energy simulation tool: http://www.doe2.com/equest/. AutodeskGreenBuildingStudio:https://gbs.autodesk.com/GBS/(cloudbased).

ENERGY MODELING AND SIMULATION SOFTWARE

- 23 TRNSYS: http://www.trnsys.com/.
- DesignBuilder: http://www.designbuilder.co.uk/.
- Radiance: Lighting simulation tool: http://www.radiance-online.org/.
- OpenStudio by NREL: https://www.openstudio.net/ (open source, free interface

TOOLS USING ENERGY PLUS AND RADIANCE

- Dymola: http://www.3ds.com/products-services/catia/products/dymola.
- Autodesk Revit (previously known as Ecotect).



Tools that Support gbXML

- CAD/BIM
 - Autodesk
 - AutoCAD Architecture & MEP
 - Revit Architecture & MEP
 - Green Building Studio (GBS)
 - Ecotect
 - Vasari
 - Bentley
 - Architecture
 - Building Mechanical Systems
 - Trimble
 - SketchUp
 - Graphisoft
 - ArchiCAD
 - Mac and Windows
- 06:31 BIMStorm
 - Rhino/Grasshopper

- HVAC/Energy/Lighting
 - Bentley Hevacomp
 - blueCAPE CFD
 - Cadsoft Envisioneer
 - Carrier
 - · Hourly Analysis Program (HAP)
 - DesignBuilder
 - DIALux
 - DOE-2.2 & eQuest (via GBS)
 - Elite Software
 - EnergySoft
 - Environmental Design Solutions Ltd.
 - Tas
 - GreenSpace Live (gModeller)
 - IES, Ltd.
 - IES <Virtual Environment>
 - Trane
 - TRACE 700







TYPICAL SOFTWARE INPUT

Table 3.3 Typical input parameters required for building energy modeling

Model input set	Input parameters
Location specific	 Local climate data (typically imported via a weather file in the software) Interior conditions and set points
Architectural massing and form	 (Typically imported through 3D geometrical modeling tools such as Google Sketchup) • Building shape and orientation • Total floor area • Number of floors and thermal zoning • Floor-to-ceiling height
Building envelope	 Window-to-wall ratio Area, orientation, solar absorptance, and thermal transmittance of all opaque building surface Area, orientation, solar heat gain coefficient, visible light and thermal transmittance, and shading of all glazing components Mass of building components Infiltration rates
Thermal and electric loads	 Lighting intensity Plug loads intensity Sensible and latent (moisture) loads from people and other equipment Pumps, motors, fans, elevators
Schedule of operations	Lighting schedulesPlug-load schedulesOccupancy schedules
Mechanical and Electrical (M&E) systems	 Cooling/Heating system type, including the source, distribution, and terminal units Ventilation system type Fan and pump inputs Economizers and/or heat recovery systems Domestic hot-water system Specialty systems (e.g. fur Renewable-energy systems

Commercial software have built-in industry standard default related to physical and technological properties, and benchmarks.

Table 3.2 Benefits of energy modeling at various stages of building development (adapted from AIA 2012)

Building stage	Energy modeling outputs
Concept design	 ✓ Define goals and requirements of the project based on early modeling results ✓ Experiment with options for building orientation, massing and envelope constructions ✓ Explore ways to reduce loads ✓ Get the design team together to assess integrated system performance and make design decisions based on the results
Schematic design	 ✓ Create a baseline energy model ✓ Test the effectiveness of different energy conservation measures and options before selection and implementation ✓ Determine the most cost effective solution to reduce energy consumption to the lowest
Design development	 ✓ Finalize baseline model to compare against proposed design ✓ Create proposed models with system alternatives to choose from ✓ Provide annual energy use charts and other performance metrics for comparing baseline versus proposed design ✓ Evaluate specific products and technologies with refined data and details
Construction documents	✓ Create documentation needed to accompany energy model results for code compliance and for green certification requirements such as LEED
Commissioning and post-occupancy	✓ Use results of the as-built model for commissioning ✓ Collect metered operating data to create a calibrated model to share with outcome-based database

Prof. Gluseppe Ridolfi, PhD


The output of the energy modeling software are values of physical aspects affecting users' comfort and natural resourses trade-off



• THERMAL ASPECTS




THERMAL ASPECTS: CLIMATE





Modeling Climate, Weather, Site, Users and Architectures.

Environmental elements that affect people's comfort




View Security

.....

NOT NATURAL FACTORS



CLIMATE a physical, socio-cultural, and technological determinant





Environmental parameters affecting thermal comfort:

- SOLAR ENERGY
- VENTILATION
- **HUMIDITY**

- radiant temperature

- air temperature

HOW TO MEASURE SOLAR ENERGY?

RADIATION=W/m2

CLIMATE DATA

We collect data near airports and other stations

Wheather data includes:


- Annual weather files (8760 hours of the year) used to compute Energy Use Intensity (EUI)
- TMY (Typical metereological year) that is encapsulated in the .epw files mantained by Energy Efficiency and Renewable Energy (EERE)
- Peak condition files used to dimension mechanical

Wheather data also includes:


geographical coordinates



Solar radiation* at the top of the atmosphere.



Solar radiation spectrum



*) Radiation occurs when an object emits electro magnetic energy.


Irradiation is the energy absorber by an object/surface

1366 W/m² (solar costant)

1 W = 3,416 Btu.

Considering the earth surface, the total solar energy is= 174 PW Peta= million of billions





Site Inventory: Physical Attributes 121





Figure 5-15 Schematic diagram of the seasonal variation in shade cast by a building in the northern hemisphere. Solar exposure in outdoor spaces near a building varies not only with weather conditions but also with time of day, day of year, and location of the space in relation to both the building and the sun.




les 24 heures Solaines

um solut
live
um solut
live ai
rrownau

Si la totalité des conditions necessaires et suffisantes n'est pas arquise, il y a desequilibre, insuffisance — malheur chaque jour et ... Toute la vic!


120 Site Analysis

Figure 5-14 Diagram of seasonal changes in the maximum daily sun angle for a mid-latitude location in the Northern Hemisphere. Source: Marsh, *Landscape Planning*, Third Ed., copyright © 1998, p. 290, Figure 15.3. Reprinted by permission of John





SOLAR ENERGY= \mathbf{f} (power, angle of incidence, sky conditions)= World Location






The influence of the site: GEOGRAPHICAL POSITION

Insolation is the sun's energy on a surface

Sun's energy depends on angle, sky conditions, volume and surfaces around.


Weather files give the total amount of *direct energy* along a year measured perpendicularly the sun direction

And diffuse energy measured getting all the energy and subtracting the direct energy capted






The influence of the site: GEOGRAPHICAL POSITION




SOLAR GEOMETRY http://andrewmarsh.com/software/sunpath-on-map-web/




The influence of the site: GEOGRAPHICAL POSITION




The influence of the site: GEOGRAPHICAL POSITION



The influence of the site: GEOGRAPHICAL POSITION



The influence of the site: GEOMETRY






The influence of the site: GEOGRAPHICAL POSITION

AVERAGE DAILY RADIATION

4: CLIMATE ANALYSIS





4.10 and 4.11

Solar roses from Central Park in New York City show the average daily amount of solar energy on each vertical segment of a cylinder. Since solar angles are symmetrical about the solstices, each season was centered on an equinox or solstice. The lower images show radiation on a horizontal surface for each hour and day of the year from the same weather file.

Source: Autodesk's Ecotect output. Courtesy of Callison.







Cloud coverage is measured as a percentage of total sky



8.2

Cloud cover in Allen, Texas, varies from intermediate and overcast in winter, to intermediate and clear in summer. The CIE defines clear skies as >70% cloud cover, overcast skies as <30% cloud cover, and other skies as intermediate.

Source: Modified output from Autodesk Ecotect Suite. Courtesy of Callison.

8.3

Actual sky conditions that correspond to overcast, intermediate, and clear skies are shown using high dynamic range (HDR) fish-eye photographs and false color images. While most daylight simulation uses synthetic, averaged sky conditions, actual sky conditions vary by the minute. HDR skies can be used in daylighting simulations, see Case Study 8.6.

Source: Inanici (2010). Images © Illuminating Engineering Society, www.ies.org.

The influence of the weather: SKY CONDITIONS

				Condizioni at	tmosferiche			
Radiazione solare	Cielo sereno	Nebbia	Nuvoloso	Disco solare giallo	Disco solare bianco	Sole appena percettibile	Nebbia fitta	Cielo coperto
		0	-0-		0	0		
globale	1000 W/m ²	600 W/m ²	500 W/m ²	400 W/m ²	300 W/m ²	200 W/m ²	100 W/m ²	50 W/m ²
diretta	90%	50%	70%	50%	40%	0%	0%	0%
diffusa	10%	50%	30%	50%	60%	100%	100%	100%

http://www.sunsim.it/




The influence of the site: Shading Mass

7.9 North Fish-eye image showing annual solar path and adjacent buildings that shade a location within an urban context. Afternoon hours in the summer are mostly shaded, while the first two hours of each day are also shaded. The peak summer cooling date is highlighted, showing full shade after 4 p.m. Source: Modified Autodesk Ecotect West East output. Courtesy of Callison. South



Visualization of sun energy radiation



Visualization of sun energy radiation






Visualization of sun energy radiation


Terrain solar exposure and solar access to evaluate the best location

5.16View Desirability, Slope
Desirability, Solar Desirability.





Irradiation analysis




7.8


Roof plan with annual solar irradiation analysis to show ideal orientations and roof forms for renewable energy collection using Autodesk Ecotect.

Source: Courtesy of Callison.


Environmental parameters affecting thermal comfort: AIR TEMPERATURE

Visualization of air temperature in relation with solar radiation





Visualization of Relative Humidity






Apparent Temperature (AT)

The **AT** is defined as the temperature, at the reference humidity level, producing the same amount of discomfort as that experienced under the current ambient temperature and humidity.

Basically the **AT** is an adjustment to the *ambient temperature* (**T**) based on the level of humidity.




	25%	30%	35%	40%	45%	50%	55%	60%	65%	70%	75%	80%	85%	90%	95%	100%
42°	48	50	52	/55		59	02	64								82
41°	48	48	51	53	轰			61	64			70	72	78	78	
40°	45	47	49	51	53	- #£.,			63			87	88	71		
33%	43	45	47	49	51	53	55	57		81					78	72
38°	10	44	45	47	49	51	53	88					64		67	69
37°	40	42	44	45	47	49	51	52	84				61	63		
36°	39	Ale	42	44	45	47	49	50	52	44	:55	57			52	
35°	37	39	10	42	44	45	47	48	50	51	53	34				
34°	36	37	39	40	42	43	45	46	48	49	51	52	-54	36	- 57	
33°	34	36	37	35	40	41	43	44	46	47	48	50	51	53	88	55
32°	33	34	36	37		40	41	42	44	45	46	48	49	50	52	53
31°	32	33	34	35	37	38	39	40	42	43	44	45	47	48	49	50
30°	30	32	33	34	35	30	37	39	40	41	42	43	45	46	47	48
29°	29	30	31	32	33	35	196	37	38	39	40	41	42	43	45	46
28°	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43
27°	27	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41
26°	26	26	27	28	29	30	31	32	33	34	34	35	36	37	38	39
25°	25	25	26	27	27	28	29	30	31	32	33	34	34	35	36	37
240	24	24	24	25	26	27	28	28	29	30	31	32	33	33	34	35
23°	23	23	23	24	25	25	26	27	28	28	29	30	31	32	32	33
22°	22	ZZ	22	- 22	25	24	25	25	26	27	27	28	29	30	30	31
THIN S	29 C°	N	essun (disagio												
Da 30	0 a 34 (Cº Si	ensazio	ne di d	lisagio											
Da 35	5 a 39 (o In	tenso	disagio	Prud	enza: I	mitare	le attiv	rità fisio	he più	pesan	ti				
	a 45 (orte se									23				
	6 a 53 (ericolo						1000							
	10.00		ericolo			A STATE OF THE STA				100						
Common Co.			CITOOO	OF THOSE	W. W	po un c	OIC! C	HISTING!	HC.							

Relationship between Temperature and Humidity

4.5


A 24-hour period set of data from a weather file shows the interaction of the dry bulb temperature, the relative humidity, the direct solar, diffuse solar, wind speed and cloud cover. Note the inverse relationship of temperature and humidity; direct and diffuse solar irradiation; and the inconsistent relationship between cloud cover and direct solar.

Source: Autodesk Ecotect Suite output of EnergyPlus weather data. Courtesy of Callison.






Wind Velocity



Effect of Wind on Temperature



HOW TO EVALUATE ENERGY PERFORMANCE

GREEN METRICS, CERTIFICATION & TARGETING



HOW TO EVALUATE ENERGY PERFORMANCE

GREEN METRICS & CERTIFICATION

Baseline solution or standardized metrics

Voluntary certifications

international sustainable building certification program

- <u>LEED</u> Leadership in Energy and Environmental Design- U.S. Green Building Council (USGBC),
- NZE Nearly Zero Energy > Net Zero Energy
- <u>LBC</u> Living Building Challenge, 2006, International Living Future Institute.
- ENERGY STAR, U.S. Environmental Protection Agency in conjunction with the U.S. Department of Energy
- NATIONAL GREEN BUILDING STANDARD, National Association of Home Builders (NAHB)
- GREENGUARD, Greenguard Environmental Institute,
- Green Globes operates in the US by the Green Building Initiative.
- PASSIVEHAUS, 1988 Adamson Lund University (Sweden) + Wolfgang Feist dell'Institut für Umwelt und Wohnen (D)

National certification by Law in Italy

- D. Lgs. 19 agosto 2005, n. 192 (attuativo della direttiva 2002/91/CE)
- L. 2006/32/CE (recepita in Italia dal D.Lgs. 115/2008, che introduce le UNI TS 11300)

2030 Framework for climate and energy



is a voulantary standard based on EUI (often 4,75 kBtu/ft2) clodes to 2020

- Fabbisogno termico per riscaldamento ≤ 15 kWh/(m²a) oppure: Carico termico specifico ≤ 10 W/m²
- Fabbisogno frigorifero per raffrescamento ≤ 15 kWh/(m²a)
- •Tenuta all'aria n₅₀ ≤ 0,6 h⁻¹
- Fabbisogno di energia primaria ≤ 120 kWh/(m²a)
- Basso surriscaldamento estivo (n. gg. < 10% con T_i > 25 °C)

Mentre è consigliato ma non obbligatorio soddisfare questi altri parametri:

- Progettazione senza ponti termici < 0,01 W/mK
- Serramenti a taglio termico U_w ≤ 0,8 W/m²K
- Impianti ad alta efficienza; ventilazione interna con recupero di calore superiore al 75%
- Ridotte dispersioni termiche per approntamento e distribuzione ACS
- Utilizzo efficiente della corrente

EUI - ANNUAL ENERGY USE INTENSITY

kBtu/sf/year kW/m2/year

allows us to run energy comparison between different buildings on a per unit area basis

Evaluation also considers in which way energy is produced inside the whole production and distribution process including looses.

For example for coal is considered a reduction of 50%

But he evaluation of CO2 emissions is more meaningful



Conversions of Common Energy Modeling Units

From Inch-Pound (IP) to the International System (SI)

1 footcandle = 10.76 Lux (illuminance; most practitioners assume 1 footcandle = 10 Lux)

1 Btu/h/ft² = 3.16 Watts/m² (instantaneous power incident on a surface)

1 Btu/ft² = 3.16 Watts* hours/m² (units of energy on a surface over time)

1 Btu = .293 Wh (unit of energy)

kBtu/ft²/year = 11.352 MegaJoules/m²/year (Energy Use Intensity, annual measure of

energy use per unit area)

1 W/ft² = .093 W/m² (Plug Load or Lighting Power Density, usually per room area)

U value = $5.678 \text{ U value (W/m}^2/^{\circ}\text{C)}$ (conductivity of a material or assembly, where

 $(Btu/ft^2/h/°F) U = 1/R)$

1 ft²/minute = .000472 m²/second (air change rate due to infiltration or fresh air supply)

1 Foot/second = .681 miles/hour = .3048 m/second = 1.097 km/hour

(speed, often in relation to airspeed)

 $^{\circ}F$ = $(5/9)^{\circ}C + 32$ (Temperature)



EUI - ANNUAL ENERGY USE INTENSITY = EDI - EPI

Energy Demand Intensity (EDI) Energy Production Intensity (EPI)

In any case we have to understand that EUI parameter doesn't return any guarantee concerning Co2 emissions








Other parameters used in energy modeling Solar Heat Gain Coefficient (SHGC)

The Solar Heat Gain Coefficient (SHGC) is a ratio of the heat transmitted through the building envelope into the building to the heat that is reflected away. SHGC is a dimensionless parameter and can theoretically range from zero to one, with one representing that all of the heat being transmitted through the envelope, and zero representing none of the incident solar heat being transmitted inside. A low SHGC would be desirable for buildings with high cooling load (e.g. tropical and hot climates), whereas a high SHGC would be beneficial for buildings with passive heating requirements (e.g. cold climate conditions).

Infiltration or Air Leakage


Infiltration or air leakage is caused by air entering or leaving the building due to unintentional gaps in the building envelope. The outside air infiltrated into the inner space would cool or heat interior spaces through convection and make the envelope insulation redundant. The air leakage from inside to outside would result in energy wastage and overload on air treatment facilities such as heating or cooling as the treated air would escape to the surroundings instead of heating or cooling the space.








EVALUATION IN RELATIONSHIP WITH DESIGN ALTERNATIVES






EVALUATION IN RELATIONSHIP WITH BASELINE SOLUTION based on current average benchmark



EVALUATION IN RELATIONSHIP WITH BASELINE SOLUTION based on current average benchmark





EVALUATION IN RELATIONSHIP WITH BASELINE SOLUTION based on Code* compliant element as a basic benchmark

*) for example: LEED certification uses ASHRAE 90.1

City	Miami	Houston	Phoenix	Atlanta	Los Angeles	Las Vegas	San Francisco	Baltimore	Albuquerque	Seattle	Chicago	Denver	Minneapolis	Helena	Duluth	Fairbanks
Medium Office	39	42	40	41	33	37	38	45	38	42	48	41	54	48	57	77
Stand- alone Retail	62	63	60	61	44	56	50	72	61	65	81	69	93	83	104	145
Quick Service Restaurant	535	549	538	561	496	541	524	609	567	575	657	604	713	663	765	949
Large Hotel	99	108	100	116	105	105	113	127	119	124	138	131	150	144	163	196
Mid-Rise Apartment	39	39	38	38	31	36	33	42	37	38	47	41	54	48	59	76



Primary Space / Building Type	Ave. % Electric	med	Site EUI 70%	90%
Education	63	58	17.4	5.8
College/University (campus-level)	63	104	31.2	10.4
Food Sales	86	193	57.9	19.3
Convenience Store (w/ or w/o gas)	90	228	68.4	22.8
Food Service	59	267	80.1	26.7
Fast Food	64	418	125.4	41.8
Restaurant/Food Market	53	207	62.1	20.7
Health Care and Outpatient	72	62	18.6	6.2
Clinic/ Other Outpatient Health	76	67	20.1	6.7
Lodging	61	72	21.6	7.2
Mall (strip mall and enclosed)	71	94	28.2	9.4
Public Assembly	57	42	12.6	4.2
Entertainment/Culture	63	46	13.8	4.6
Library	59	92	27.6	9.2
Recreation	55	39	11.7	3.9
Social/Meeting	57	43	12.9	4.3
Public Order & Safety	57	82	24.6	8.2
Fire Station/Police Station	56	82	24.6	8.2
Service (vehicle repair/postal service)	63	45	13.5	4.5
Storage/Shipping/ Non-refrigerated warehouse	56	10	3.0	1.0
Retail Store (non-mall stores, vehicle dealerships)	67	53	15.9	5.3
Other (varies greatly)	56	70	21.0	7.0

Targets based on U.S. Commercial Building National Average

Energy Use Intensity (EUI) Targets, U.S. Commercial Buildings, National Averages, kBtu/ft²-yr
Use for occupancy types not in "EPATarget Finder" or in "Energy
Use Intensity (EUI) Targets, by Building Type and Climate Zone."

Derived from Architecture 2030 (2012), based on EPA (2011) and Energy Information Administration's Commercial Building Energy Use Survey (CBECS), 2003; using the EPA's Table 1: 2003 CBECS National Average Source Energy Use and Performance Comparisons by Building Type.



ASHRAE Climate Zones	City		Small Office 5.500 sf / 1story			Medium Office 53,628 sf / 3 story			Large Office 498.588 sf / 12 story			Medical Office 40.946 sf / 3 story			Primary School 73.960 sf / 1 story			Secondary School 210,887 sf / 2 story		Hospital (general	medical & surgical) 241.351 sf / 5 st			Senior Care Facility 20,025 sf / 1 story			Hotel (small) 43,200 sf / 4 story	
				90%		70%	-		70%	90%		70%			70%			70%	90%			90%		70%				
1A	Honolulu, HI	64	19	6	91	27	9	107	32	11	155	47	16	42	13	4	74	22	7	302	91	30	157	47	16	82	25	8
1A	San Juan, PR	53	16	5	75	23	8	88	26	9	185	56	19	27	8	3	51	15	5	172	52	17	105	32	11	56	17	6
1A	Miami, FL	63	19	6	89	27	9	105	32	11	140	42	14	49	15	5	76	23	8	266	80	27	140	42	14	73	22	7
2A	Houston, TX	61	18	6	88	26	9	103	31	10	122	37	12	59	18	6	76	23	8	256	77	26	135	41	14	72	22	7
2B	Phoenix, AZ	68	20	7	96	29	10	112	34	11	173	52	17	72	22	7	107	32	11	305.	92	31	163	49	16	89	27	9
3A	Atlanta, GA	57	17	6	84	25	8	99	30	10	95	29	10	59	18	6	62	19	6	239	72	24	125	38	13	67	20	7
3B-CA	Los Angeles, CA	47	14	5	74	22	7	90	27	9	69	21	7	65	20	7	55	17	6	249	75	25	120	36	12	57	17	6
3B-other	Las Vegas, NV	65	20	7	84	25	8	108	32	11	140	42	14	74	22	7	93	28	9	289	87	29	153	46	15	84	25	8
30	San Francisco	51	15	5	78	23	8	94	28	9	73	22	7	62	19	6	60	18	6	247	74	25	123	37	12	64	19	6
4A	Baltimore, MD	59	18	6	85	26	9	101	30	10	91	27	9	60	18	6	58	17	6	233	70	23	123	37	12	70	21	7
4B	Albuquerque, NM	61	18	6	88	26	9	104	31	10	106	32	11	74	22	7	73	22	7	266	.80	27	140	42	14	79	24	8
4C	Seattle, WA	57	17	6	84	25	8	100	30	10	82	25	8	67	20	7	60	18	6	247	74	25	129	39	13	74	22	7
5A	Chicago, IL	73	22	7	104	31	10	122	Milita	12	113	34	11	88	26	9	79	24	78	263	79	26	152	46	15	92	28	9
5B	Boulder, CO	63	19	6	90	27	9	106	32	11	101	30	10	74	22	7.	66	20	7	257	77	26	139	42	14	83	25	8
, 5C	Ketchican, AK	66	20	7	93	28	9	109	33	11	97	29	10	55	17	6	72	7 22	7	246	74	25	138	41	14	89	27	9
6A	Minneapolis, MN	77	23	8	108	32	11	126	38	13	121	36	12	89	27	9	80	24	8	263	79	26	156	47	16	97	29	10
6B	Helena, MT	65	20	7	92	28	9	108	32	11	98	29	10	72	22	7	62	19	6	250	75	25	138	41	14	86	26	9
7	Duluth, MN	78	23	8	110	33	11	108	32	11	114	34	11	85	26	9	73	22	7	254	76	25	153	46	15	101		10
7.5	Kenai, AK Fairbanks, AK	70	21	7	97	29 31	10	113	34	11	105	32	11	56 69	17	6	73 64	19	6	246	74	25 25	141	42	14	96	32	10

Energy Use Intensity (EUI) Targets, by Building Type and Climate Zone, kBtu/ft²-yr na = not available in EPA "Target Finder"



	Hotel (large) 12,202 sf / 6 story			Residence Hall / Dormitory 100,000 sf / 4 story			Mid-Rise Apartment 33.740 sf / 4 story		Warehouse	(unrefrigerated)	52,045 st / 1 story	Warehouse	(refrigerated)	52,045 sf / 1 story		Courthouse, federal 395,000 sf.		Bank / Financial	Institution	4,100 sf / 1 story branch		Supermarket / Grocery 45,000 sf / 1 story		equ	Retail 24,962 sf / 1 story			Strip Mall 22500 sf / 1 story			House of Worship 17,000 sf / 1 story	
med	70%	90%	med	70%	90%	med	70%	90%	med	70%	90%	med	70%	90%	med	70%	90%	med	70%	90%	med	70%	90%	med	70%	90%	med	70%	90%	med	70%	90%
111	33	11	102	31	10	na	na	na	27	8	3	174	52	17	107	32	11	112	34	11	384	115	38	72	22	7	na	na	na	29	9	3
74	22	7	72	22	7	na	na	na	21	6	2	139	42	14	88	26	9	92	28	9	274	82	27	63	19	6	na	na	na	21	6	2
99	30	10	92	28	9	39	12	4	23	7	2	149	45	15	105	32	11	110	33	11	280	84	28	73	22	7	56	17	6	26	8	3
98	29	10	88	26	9	39	12	4	24	7	2	127	38	13	103	31	10	108	32	11	264	79	26	73	22	7	58	17	6	25	8	3
118	35	12	118	35	12	38	11	4	30	9	3	180	54	18	112	34	11	117	35	12	410	123	41	77	23	8	57	17	6	34	10	3
92	28	9	77	23	8	38	11	4	24	7	2	94	28	9	99	30	10	104	31	10	230	69	23	71	21	7	62	19	6	20	6	2
86	26	9	58	17	6	31	9	3	24	7	2	62	19	6	90	27	9	95	29	10	229	69	23	59	18	6	44	13	4	8	2	1
113	34	11	105	32	11	36	11	4	30	9	3	147	44	15	108	32	11	113	34	11	371	111	37	75	23	8	57	17	6	30	9	3
93	28	9	67	20	7	33	10	3	27	8	3	56	17	6	94	28	9	99	30	10	245	74	25	65	20	1	53	16	5	13	4	1
95	29	10	82	25	8	42	13	4	26	8	3	80	24	8	101	30	10	106	32	11	228	68	23	75	23	8	74	22	7	22	7	2
108	32	11	94	28	9	37	11	4	31	9	3	98	29	10	104	31	10	109	33	11	322	97	32	75	23	8	64	19	6	25	8	3
102	31	10	82	25	8	38	11	4	31	9	3	58	17	6	100	30	10	105	32	11	275	83	28	73	22	7	69	21	7	20	6	2
123	37	12	112	34	11	47	14	5	42	13	4	102	31	10	122	37	12	128	38	13	257	77	26	109	33	11	85	26	9	36	11	4
112	34	11	101	30	10	41	12	4	34	10	3	78	23	8	106	32	11	111	33	11	319	96	32	79	24	8	72	22	7	27	8	3
118	35	12	113	34	11	na	na	na	38	11	4	56	17	6	109	33	11	114	34	11	320	96	32	86	26	9	na	na	na	31	9	3
128	38	13	126	38	13	54	16	5	45	14	5	102	31	10	126	38	13	132	40	13	270	81	27	115	35	12	99	30	10	41	12	4
115	35	12	107	32	11	48	14	5	36	11	4	64	19	6	108	32	11	113	34	11	318	95	32	83	25	8	89	27	9	29	9	3
132	40	13	133	40	13	59	18	6	48	14	5	78	23	8	128	38	13	133	40	13	266	80	27	120	36	12	111	33	11	43	13	4
124	37	12	130	39	13	na	na	na	41	12	4	56	17	6	113	34	11	118	35	12	340	102	34	91	27	9	na	na	na	36	11	4
135	41	14	163	49	16	76	23	8	45	14	5	57	17	6	120	36	12	125	38	13	373	112	37	99	30	10	156	47	16	44	13	4

Energy Use Intensity (EUI) Targets, by Building Type and Climate Zone, $kBtu/ft^2$ -yr na = not available in EPA "Target Finder"



Commercial Space / Building Type		Site EUI		Commercial Space / Building Type		UI kWh/m	² , уг. 90%
	med	70%	90%		med	70%	90%
ATLANTIC				MANITOBA		403.0	47.7
Nholesaie Trade	436.1	130.8	43.6	Wholesale Trade	433.4	130.0	43.3
Retail Trade	525.0	157.5	52.5	Rotall Trade	527.8	1583	52.B
Transportation & Warehousing	319.5	95.8	31.9	Transportation & Warehousing	394.5	118.3	39.4
information & Cultural Industries	558.4	167.5	55.8	Information & Cultural Industries	536.9	161,7	83.9
Offices	405.6	121.7	40.6	Offices	422.3	126.7	42.2
Educational Services	444.5	133.3	44.4	Educational Services	488.2	145.8	48.6
Healthcare & Social Assistance	738.9	221.7	73.0	Healthcare & Social Assistance	780.8	234.2	78.1
Arts, Entertainment & Recreation	497.3	149.2	49.7	Arts, Entertainment & Recreation	458.4	137.5	45.8
Accommodation & Food Service	719.5	215.9	72.0	Accommodation & Food Service	794.5	238.4	79,5
Other Services	391.7	117.5	39.2	Other Services	463.9	139.2	46.4
QUEBEC	15,	1		SASKATCHEWAN			9
Wholesale Trade	527,8	168.3	52.8	Wholesale Trade	566.7	170.0	56.7
Retall Trade	563.9	169.2	56.4	Retail Trade	725.1	217.5	72.5
Transportation & Warehousing	452.8	135.8	45.3	Transportation & Warehousing	497.3	149.2	49.7
Information & Cultural Industries	780.6	234.2	76.1	Information & Cultural Industries	711.2	213.4	71.1
Offices	452.8	135.8	45.3	Offices	563.9	169.2	58.4
Educational Services	561.2	168.3	583	Educational Services	600,0	180.0	50.0
Healthcare & Social Assistance	905.6	271.7	90.6	Healthcare & Social Assistance	788.2	235.9	78.6
Arts, Entertainment & Recreation	661.2	198.3	66.1	Arts, Entertainment & Recreation	583.4	175.0	58.3
Accommodation & Food Service	894.5	268.4	89.5	Accommodation & Food Service	827.8	248.4	82.6
Other Services	505.6	151.7	50.6	Other Services	563.9	159.2	55 4
ONTARIO		THE RESERVE		ALBERTA			9
Wholesale Trade	463.9	139.2	46.4	Wholesale Trade	413.9	124.2	41.4
Setail Trade	489.5	140.8	46.9	Retail Trade	500.0	190.0	50.0
Transportation & Warehousing	394.5	118.3	39.4	Transportation & Warehousing	369.5	110.8	36.9
Information & Cultural Industries	444.5	133.3	44.4	Information & Cultural Industries	506.4	152.5:	50.8
Offices	397.3	119.2	39.7	Offices	380.6	114.2	38.1
Educational Services	452.8	135.8	45.3	Educational Services	425.0	127.5	42.6
Healthcare & Social Assistance	697.3	209.2	69.7	Healthcare & Social Assistance	616.7	185.0	61.7
Arts, Entertainment & Recreation	502.8	150.8	50.3	Arts, Entertainment & Recreation	483.9	129.2	46.
Accommodation & Food Service	666.7	200.0	66.7	Accommodation & Food Service	725.1	217.5	72.5
Other Services	436:1	130.8	43.6	Other Services	391.7	117.5	39.0


Energy Use Intensity (EUI) Targets, Canadian

Commercial Buildings, Provincial Averages, kWh/m²/yt

Efficiency, Comp

Multiply kWh x 2

Derived from Natural Resources Canada, Office of Energy Efficiency, Comp.



The 2030 Challenge Targets


The Architecture 2030 Challenge allows up to 20% of the overall energy reduction to come from off-site renewable energy. The carbon-neutral target uses no fossil fuel/GHG-emitting energy to operate.



5

For the kick-off eco-charette for the Ever Vall project, nearly 40 people representing all disciplines gathered to thrash out ideas to achieve sustainable project goals. The masterplan for Ever Vall achieved LEED for Neighborhood Development. (MIND Platform Stare 2 certification.

Note: Photos, renderings, and data are courtesy of Vall Resorts Development Company and may not be reproduced without permission.



5.5

Early diagrams by Lake Flato Architects explore the site and massing options. Source: Courtesy of Lake Flato Architects and Austin Central Library.

Daylight Programming Matrix

Noon Sun Angles: June 66° Sept/Mar: 42° Dec: 19° Primary Design Sky Condition: overcast

Program Element	Occupancy Time and Duration	ls Daylight Important ?	Are Views to the Exterior Important?	Is Direct Sunlight Control Needed?	Is Glare Control Crucial?	Is Space Darkening Required?	Design Illumination ?	Ideal Daylight Aperture Strategy?	ideal Solar Orientation?	Organization on Site?
open office	82m-6pm	Y	Y	Y	Y	N	20fe,	side/	Nors	-
private office	82m-6pm	Y	Y	Y	Υ	N	20-fc 2mbrat 35 fc bek	side/ top	individual individuals	open office
large conf.	100m-6pm	Y	Y	Y	Y	Y	30 fc	side		interior, with views
lobby/recept.	82m-5pm	Y	Y	st rece	ption	N	15 fc	side/ top	Nors	grand floor
training space	82m - 5pm	N	Y	Y	Y	Y	20fc	side		Merior, with views



Energy	Design Target		Median Building	
Energy Performance Rating (1-100)	N/A	99	50	
Energy Reduction (%)	N/A	80	0	
Source Energy Use Intensity (kBtu/Sq. Ft./yr)	N/A	89	222	
Site Energy Use Intensity (I/Stu/Sq. Ft /vr)	NA	41	103	
Total Annual Source Energy (kStu)	N/A	10,659,154	26,647,885	
Total Annual Site Energy (k8tu)	N/A	4,947,347	12,368,369	
Total Annual Energy Cost (\$)	N/A	\$ 68,324	\$ 170,811	
Pollution Emissions				
CO2-eq Emissions (metric tons/year)	NVA	745	1,361	
CO2-eq Emissions Reduction (%)	N/A	80%	0%	

Facility Information 81658 United States					7 Ed	
Facility		Estimated Design Energy			Edil	
Characteristic Space Type	Gross Floor Area (Sq. Ft.)	Energy Source	Units	Estimated Total Annual Energy Use	Energy Rate (\$/Unit)	
Hotel	120,000	Electricity - Grid Purchase	kBtu	N/A	\$ 0.020/kBtu	
Total Gross Floor Area	120,000					
		Natural Gas	kBtu	N/A	\$ 0.009/49tu	
The Median Building is e Performance Rating of 50	quivalent to an EPA Energy	Source Data as Description.	sapted fr	om DOE-EIA. See t	EPA Tectnical	

5.3

Target-Finder output for a hotel in Vail, Colorado. Target-Finder displays several types of metrics: Site, Source, Cost, and Carbon Emissions. This information is based on the Commercial Building Energy Consumption Survey (CBECS) data.

Source: https://www.energystar.gov/index.cfm?fuseaction=target_finder.



In any case the optimized solution is a compromise between different aspects





Fig. 4.4 Massing options and implication on building performance (Sefaira 2013)





Thinking in terms of both analysis and context

Form is often conventionally understood in architectural terms as the pattern that configures parts within the whole. Many, if not most, ways of understanding these formal patterns involve techniques of analysis that break down, dissect or deconstruct the larger whole into its constituent elements or their fundamental arrangements and relationships. The *analytic method* is a valid approach, from which one can learn much about buildings. It can be thought of as moving from higher to lower levels of complexity in the maps. Analysis is true and correct in that it describes one portion or aspect of design, however, alone it is incomplete and insufficient in two ways:

- The emergent qualities unique to the whole are never found via analysis, only those qualities found in the parts.
- 2) Atomistic analysis misses how the whole is simultaneously a part of something larger.

The *yin* of analysis's *yang* is *holism* and *contextualism*. To understand anything as a whole, one has to look for what is unique to the whole and not found in the parts. The *contextual method* looks for the larger whole to which a part contributes. One way this is often done in design is by mapping the pattern that defines the whole, that is representing the *relationships* among the parts. In addition to breaking it down, one can understand the whole by placing it within its larger, containing context where it becomes a part of a whole larger than itself.

Designing is mapping the pattern that defines the whole, that is representing the relationships among the parts

The contextual method represents relationships between the parts.
It can comprehend the wholeness

Building Layout and Massing


"Massing" is the architectural term used when determining the overall layout (e.g. compact or spread-out), shape (e.g. square, rectangle, oval), size (e.g. height, length, width) and form factor (more solid or porous with cut-outs) of the building. Massing choices depend on the project specifics such as the project site and its goals. It should be optimized in the early stages of the building along with its location and orientation. Successful massing for green buildings would help to reduce energy loads for the building by leveraging on the natural effects such as the wind flow patterns and the sun path.

Apart from reducing energy use, a good massing and orientation can also help in rainwater harvesting, integrating the building with urban planning provisions, reducing material usage and in protecting ecologically sensitive elements such as greenery, trees and ponds. Modelling and simulation tools as described in the earlier chapter can be used to assess the performance of the building with various orien-tation and massing choices. Figure 4.4 shows the impact of different massing options on the building's energy use intensity, operating costs and daylight potential.



Workflow Part 1: Goals, Metrics, and Analysis Tools

Sun and Shadow Studies for High Performance Building Design





Autodesk Sustainability Workshop

Autodesk^{*}




Level 3 – Space & Zone Thermal Properties













ENERGY CONCEPTUAL MASS MODELING: A NEW WAY TO DESIGN

Level 3 – Overall Energy Model Geometry Accuracy










An illustration of FormIt conceptual mass models suited (and not) for Energy Analysis













Level 3 Overview - Scales from Concept to Detail






Architectural & Energy Analytical Model elements...








Prof. Gluseppe Ridolfi, PhD

What is Green Building XML (gbXML)?

An open XML schema that allows for the exchange of building data from modeling to analysis software tools and back




- Interoperability is the key to successfully using BIM software tools
 - It minimizes the human involvement and translation errors




12 STEPS PASSIVE STRATEGIES IN MASS MODELING




1- Find your climate zone








2- Tune-Up your climate zone considering the climate evolution and site



3. Select the main energy behaviour according with climate zone






To be cooled

To be heated



4. Confirm the main energy behaviour with conceptual energy analysis






7.3 Temperature Method.

Annual temperature profile, with estimated heating and cooling seasons highlighted.

Source: Ecotect outputs of annual weather data from Central Park in New York City.

5. Select the mass types according to functional destination, architectural image, energy consideration,…



Short Fat/Thick (internal load dominant) are the current type for commercial buildings, manufacturing,...

Short Thin/Skin (skin dominant) are the current type for housing schools,..

Tall Fat/Thick ((internal load dominant) are the current type for hospitals, offices,...

Tall Thin/Skin (skin dominant) are the current type for housing, offices, schools,...

Compact or Thick buildings have less dissipation and works better in cold climate, but have a limited possibilities for passive design

Skin dominant buildings allows a better ventilation and daylight, but have an higher dissipation. They works fine for passive design

Tall buildings have less roof solar radiation, better for cooling strategies

Compact or **Thick** buildings have less dissipation and works better in cold climate, but have a limited possibilities for passive design

Skin dominant buildings allows a better ventilation and daylight, but have an higher dissipation. They works fine for passive design

6. Define the main energy strategies according with mass types

CLIMATE	PERCEIVED CLIMATIC CONDITION	ILD/THICK BUILDING	SLD/THIN BUILDING	OUTDOOR ROOMS
COLD	Heating Dominated	C + H-hu C + H-ar	C	C2
MIXED	Combined Heating & Cooling	H–hu H–ar	C + H–hu C + H–ar	С
HOT HUMID	Cooling Dominated: Humid	H2-hu	H-hu	C + H-hu
HOT ARID	Cooling Dominated: Arid	H2-ar	H-ar	C + H–ar
4 2 1 1 1 1 1		HIGH INTERNAL GAINS	LOW INTERNAL GAINS	NO INTERNAL GAINS

ILD= Internal-Load-Dominated
SLD=Skin-Load Dominated
C=Cold Bundle

H=Hot Bundle

ar=arid

hu=ventilated dominated


H2=very hot, heavily cooling dominated

C2=heavily heating dominated



7. Tuneup the energy strategy according to more detailed analysis

COOLING vs HEATING: a detailed estimation using Shoebox model



7.4

Shoebox Model Method.

Monthly energy use profile for an office floor plate in New York


City. The simulation was performed in Green Building

Studio using a shoebox model.

A simple, automated shoebox model can generate a more accurate illustration of months requiring shading design. For this analysis, a thermal zone with glazing was uploaded from Autodesk Ecotect to the Green Building Studio to run an EnergyPlus simulation. Months where cooling energy is high (3) are chosen for shading. This example seems to require more cooling than the temperature method example because the shoebox model uses an office typology, where people, equipment, and lighting add heat during the day.



8. Model the context





5,10

Completed wind speed studies were used to mass new structures to block undesirable winter winds through public plazas. This study was completed as part of the Cambridge Master Plan in Boston, using Autodesk Vasari 3D for a Computational Fluid Dynamics simulation, with false colors representing wind speed. Wind is simulated to come from the upper left.

Source: Courtesy of CBT Architects and Planners.

Rapporto superficie/volume


Distribuzione urbana densa vs compatta Alti edifici vs bassi Edifici compatti vs bassi



9. Model mass alternatives

Massing


An early step in site planning involves massing the program into geometrical blocks driven by typology, such as linear, double-loaded residential towers and hotels, which tend to be bar buildings between 60' and 75' wide. Most other typologies have standard widths or depths. A shoebox model of one or more typical widths can be used to study skin-to-core depth, orientation, glazing percentage, or other aspects.



5.11


HMC Architects in-house energy simulations specialists, ArchLab, used eQuest to analyze various single- and double-loaded classroom layouts for overall energy use. This study was done using common room layouts and energy data from existing buildings, and serves as a reference for many other projects as well. The team learned that self-shading has a larger impact on energy use than orientation. Over 50 configurations were compared in each of the four orientations, with the team settling on a design with a U-shaped courtyard.






When Modern Movement used the North-South orientation (+19°)

Le Corbousier, Plan of La ville de 3 million d'habitants






New orientation for Temperate Climate





Orientamento	Periodo estivo	Periodo invernale	
Finestre a sod-est	Molto soleggiate - Raggi quasi orizzontali	Molto soleggiate - Raggi qua: orizzontali	
Finestre a sud-ovest	Molto soleggiate - Raggi quasi orizzontali	Molto soleggiate - Raggi quas orizzontali	
Finestre a est		Raggi orizzontali	
Finestre a ovest		Raggi orizzontali	
Finestre a nord	Poco soleggiata		
Finestre a sud	Raggi quasi verticali	Raggi orizzontali	
Finestre a nord e nord-ovest	Raggi perpendicolari	Assenza di raggi solari	




TEMPERATE: exposed facade to South-East-(West)

COLD: exposed facade to West and South with big windows an low sill

ARID: small high windows exposed to East and North to in order to avoid ground radiation

HOT-HUMID: Windows exposed to North-South in order to take advantage of the big pressure difference for ventilation.




- More orientation flexibility in temperate, hot humid and tropical-humid climate
- Consider to obtain breezy street for hot climate,
- Evaluate the effect of dense or desperse urban fabric







Ratio of the ground area between building to the total surface area of the ground and walls




Prof. Gluseppe Ridolfi, PhD
















12. Update the building model: spazial zone and thermal block






12. Update the building model: building hight




12. Update the building model: building hight






Level 3 - Exterior Shading










SHADING VOLUMES FROM THE CONTEXT


7.5

Climate Consultant software allows a quick interactive estimation of shading effectiveness at various orientations and shading depths.

Source: Courtesy of UCLA Energy Design Tools Group, http://www.energy-designtools.aud.ucla.edu/.







LINKS

Climate Analysis

(https://sustainabilityworkshop.autodesk.com/buildings/climate-analysis)

Solar Position

(https://sustainabilityworkshop.autodesk.com/buildings/solar-position)

The Solar Envelope

(http://www-bcf.usc.edu/~rknowles/sol_env/sol_env.html#anchor471853)

Reading Sun Path Diagrams [video]

(https://sustainabilityworkshop.autodesk.com/buildings/reading-sun-path-diagrams)

Sun and Shadow Studies in BIM

(https://sustainabilityworkshop.autodesk.com/buildings/sun-and-shadow-studies-bim)

Sun and Shadow Studies in BIM -Workflow [video]

(https://www.youtube.com/watch?time_continue=317&v=_LrjmknwPyg)

The difference between source and site energy

(https://www.energystar.gov/buildings/facility-owners-and-managers/existing-buildings/use-portfolio-manager/understand-metrics/difference)

Revit Tutorials: Conceptual Massing

(https://www.youtube.com/watch?v=00Uo8glc1YU)

Revit Tutorials: Design Options

(https://www.youtube.com/watch?v=b1zNYwjnVPA)

Revit Design Options 1 of 3 [video]

(https://www.youtube.com/watch?v=cGelwjOAvPI)

Energy Analysis Workflows in Revit

(http://help.autodesk.com/view/BUILDING_PERFORMANCE_ANALYSIS/ENU/?guid=GUID-E85A114E-BA0D-4811-B1A5-4EE26462708A)

Revit Energy Analysis Webinar [video] (https://www.youtube.com/watch?v=nFdW913mgLl)

Building Performance Analysis in Revit 2016 R2 with Autodesk Insight 360 (http://www.aecbytes.com/tipsandtricks/2015/issue76-revit.html)

examples

Italian Nursery School: Conceptual Design Analysis

(https://sustainabilityworkshop.autodesk.com/project-gallery/italian-nursery-school-conceptual-design-analysis)

Sustaining Modernity: An Analysis of The Gropius House

(https://sustainabilityworkshop.autodesk.com/project-gallery/sustaining-modernity-analysis-gropius-house)